

## **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application:

### **Listing of Claims:**

- 1           1.       (Currently amended) A method for displaying multiple two-  
2       dimensional (2D) windows with related content within a three-dimensional (3D)  
3       display model, comprising:  
4           receiving a command to display a first window within the 3D display  
5       model;  
6           displaying content of the first window on a first surface of a 3D object;  
7           receiving a command to display a second window within the 3D display  
8       model, wherein content of the second window is related to content of the first  
9       window;  
10          looking up an identifier for the second window in a lookup table that  
11       contains entries specifying relationships between windows;  
12          determining if the second window is related to the first window;  
13          if so, displaying content of the second window on the second surface of  
14       the 3D object; and  
15          if not, displaying content of the second window on a surface of a distant  
16       3D object, which is not located in close proximity to the 3D object in the 3D  
17       display model.  
18          ~~displaying content of the second window on a second surface of the 3D~~  
19       ~~object;~~  
20          ~~receiving a notification that the first window and the second window~~  
21       ~~contain related content; and~~

22        ~~creating an association between the first window and the second window~~  
23   ~~in a lookup table.~~

1            2.        (Original) The method of claim 1, wherein the second surface of  
2   the 3D object is located on the opposite side of the 3D object from the first  
3   surface, and wherein only one of the first surface of the 3D object and the second  
4   surface of the 3D object is visible at any given time.

1            3.        (Original) The method of claim 2, further comprising rotating the  
2   3D object so that the second surface is visible.

1            4.        (Original) The method of claim 1, further comprising:  
2   receiving a command to display a third window within the 3D display  
3   model; and  
4   displaying content of the third window on a surface of a second 3D object,  
5   wherein the second 3D object is located in close proximity to the 3D object in the  
6   3D display model.

1            5.        (Original) The method of claim 2, further comprising:  
2   receiving a modal dialog related to the content of the first window,  
3   wherein the modal dialog must be responded to before any other action may be  
4   taken on an application;  
5   rotating the 3D object so that the second surface is visible and the first  
6   surface is hidden; and  
7   displaying the modal dialog on the second surface.

1           6.       (Original) The method of claim 5, further comprising rotating any  
2 related 3D objects so that related content on the surface of the related 3D objects  
3 is not visible until the modal dialog is acknowledged.

1           7.       (Original) The method of claim 1, wherein the first window and the  
2 second window are associated with different applications.

1           8.       (Cancelled)

1           9.       (Cancelled)

1           10.      (Original) The method of claim 4, wherein the 3D object is stacked  
2 on top of the second 3D object so that the second 3D object is obscured by the 3D  
3 object from the viewpoint of a user.

1           11.      (Original) The method of claim 10, wherein the 3D object is  
2 translucent so that the second 3D object is visible through the 3D object.

1           12.      (Currently amended) A computer-readable storage medium storing  
2 instructions that when executed by a computer cause the computer to perform a  
3 method for displaying multiple two-dimensional (2D) windows with related  
4 content within a three-dimensional (3D) display model, the method comprising:  
5           receiving a command to display a first window within the 3D display  
6 model;  
7           displaying content of the first window on a first surface of a 3D object;  
8           receiving a command to display a second window within the 3D display  
9 model, wherein content of the second window is related to content of the first  
10 window;

11        looking up an identifier for the second window in a lookup table that  
12        contains entries specifying relationships between windows;  
13        determining if the second window is related to the first window;  
14        if so, displaying content of the second window on the second surface of  
15        the 3D object; and  
16        if not, displaying content of the second window on a surface of a distant  
17        3D object, which is not located in close proximity to the 3D object in the 3D  
18        display model.  
19        ~~displaying content of the second window on a second surface of the 3D~~  
20        ~~object;~~  
21        ~~receiving a notification that the first window and the second window~~  
22        ~~contain related content; and~~  
23        ~~creating an association between the first window and the second window~~  
24        ~~in a lookup table.~~

1            13.        (Original) The computer-readable storage medium of claim 12,  
2        wherein the second surface of the 3D object is located on the opposite side of the  
3        3D object from the first surface, and wherein only one of the first surface of the  
4        3D object and the second surface of the 3D object is visible at any given time.

1            14.        (Original) The computer-readable storage medium of claim 13,  
2        wherein the method further comprises rotating the 3D object so that the second  
3        surface is visible.

1            15.        (Original) The computer-readable storage medium of claim 12,  
2        wherein the method further comprises:  
3            receiving a command to display a third window within the 3D display  
4        model; and

5 displaying content of the third window on a surface of a second 3D object,  
6 wherein the second 3D object is located in close proximity to the 3D object in the  
7 3D display model.

1 16. (Original) The computer-readable storage medium of claim 13,  
2 wherein the method further comprises:  
3 receiving a modal dialog related to the content of the first window,  
4 wherein the modal dialog must be responded to before any other action may be  
5 taken on an application;  
6 rotating the 3D object so that the second surface is visible and the first  
7 surface is hidden; and  
8 displaying the modal dialog on the second surface.

1 17. (Original) The computer-readable storage medium of claim 16,  
2 wherein the method further comprises rotating any related 3D objects so that  
3 related content on the surface of the related 3D objects is not visible until the  
4 modal dialog is acknowledged.

1 18. (Original) The computer-readable storage medium of claim 12,  
2 wherein the first window and the second window are associated with different  
3 applications.

1 19. (Cancelled)

1 20. (Cancelled)

1           21.     (Original) The computer-readable storage medium of claim 15,  
2 wherein the 3D object is stacked on top of the second 3D object so that the second  
3 3D object is obscured by the 3D object from the viewpoint of a user.

1           22.     (Original) The computer-readable storage medium of claim 21,  
2 wherein the 3D object is translucent so that the second 3D object is visible  
3 through the 3D object.

1           23.     (Currently amended) An apparatus for displaying multiple two-  
2 dimensional (2D) windows with related content within a three-dimensional (3D)  
3 display model, comprising:  
4           a receiving mechanism configured to receive a command to display a first  
5 window within the 3D display model;  
6           a display mechanism configured to display content of the first window on  
7 a first surface of a 3D object;  
8           wherein the receiving mechanism is further configured to receive a  
9 command to display a second window within the 3D display model, wherein  
10 content of the second window is related to content of the first window;  
11           a lookup mechanism configured to lookup an identifier for the second  
12 window in a lookup table that contains entries specifying relationships between  
13 windows; and  
14           a determination mechanism configured to determine if the second window  
15 is related to the first window;  
16           wherein the display mechanism is further configured to display content of  
17 the second window on the second surface of the 3D object if the second window  
18 is related to the first window; and  
19           wherein the display mechanism is further configured to display content of  
20 the second window on a surface of a distant 3D object, which is not located in

21 close proximity to the 3D object in the 3D display model, if the title of the second  
22 window is not related to an identifier for the first window.

23 ~~wherein the display mechanism is further configured to display content of~~  
24 ~~the second window on a second surface of the 3D object;~~

25 ~~a notification mechanism configured to receive a notification that the first~~  
26 ~~window and the second window contain related content; and~~

27 ~~an association mechanism configured to create an association between the~~  
28 ~~first window and the second window in a lookup table.~~

1           24.     (Original) The apparatus of claim 23, wherein the second surface  
2 of the 3D object is located on the opposite side of the 3D object from the first  
3 surface, and wherein only one of the first surface of the 3D object and the second  
4 surface of the 3D object is visible at any given time.

1           25.     (Original) The apparatus of claim 24, further comprising a rotation  
2 mechanism configured to rotate the 3D object so that the second surface is visible.

1           26.     (Original) The apparatus of claim 23, wherein the receiving  
2 mechanism is further configured to receive a command to display a third window  
3 within the 3D display model, and wherein the display mechanism is further  
4 configured to display content of the third window on a surface of a second 3D  
5 object, wherein the second 3D object is located in close proximity to the 3D  
6 object in the 3D display model.

1           27.     (Original) The apparatus of claim 24, further comprising:  
2 wherein the receiving mechanism is configured to receive a modal dialog  
3 related to the content of the first window, wherein the modal dialog must be  
4 responded to before any other action may be taken on an application; and

5 a rotation mechanism configured to rotate the 3D object so that the second  
6 surface is visible and the first surface is hidden;  
7 wherein the display mechanism is further configured to display the modal  
8 dialog on the second surface.

1 28. (Original) The apparatus of claim 27, wherein the rotation  
2 mechanism is further configured to rotate any related 3D objects so that related  
3 content on the surface of the related 3D objects is not visible until the modal  
4 dialog is acknowledged.

1 29. (Original) The apparatus of claim 23, wherein the first window and  
2 the second window are associated with different applications.

1 30. (Cancelled)

1 31. (Cancelled)

1 32. (Original) The apparatus of claim 26, wherein the 3D object is  
2 stacked on top of the second 3D object so that the second 3D object is obscured  
3 by the 3D object from the viewpoint of a user.

1 33. (Original) The apparatus of claim 32, wherein the 3D object is  
2 translucent so that the second 3D object is visible through the 3D object.

1 34. (New) The method of claim 1, further comprising:  
2 receiving a notification that the first window and the second window  
3 contain related content; and



4           creating an association between the first window and the second window  
5   in a lookup table.

1           35.   (New) The computer-readable storage medium of claim 12,  
2   wherein the method further comprises:  
3           receiving a notification that the first window and the second window  
4   contain related content; and  
5           creating an association between the first window and the second window  
6   in a lookup table.

1           36.   (New) The apparatus of claim 23, further comprising:  
2           a notification mechanism configured to receive a notification that the first  
3   window and the second window contain related content; and  
4           an association mechanism configured to create an association between the  
5   first window and the second window in a lookup table.